



Open-Ended "M"



Specifications

Widths (mm) <small>In between widths available</small>	10	15	20	25	30	50	85	100
Lengths	Any lengths available - Stock rolls 30 meters							
Available Options	Nylon coating tooth side (PAZ), Nylon backing (PAR), Nylon both sides (PAZ-PAR)							
Tension Member Options	High Power (HP) Steel High Flex (HF) Steel							



Spliced and Welded "V"



Specifications

Widths (mm) <small>In between widths available</small>	15	20	25	30	50	85	100
Min. Joined Length (mm) <small>Increasing in one tooth increments</small>	1,150						
Available Options	Nylon coating tooth side (PAZ), Nylon backing (PAR), Nylon both sides (PAZ-PAR)						
Tension Member Options	High Flex (HF) Steel						

Specifications

Timing Belt	Pitch (mm)	Code	Ultimate Tensile Strength (N/10mm belt width)	Maximum Allowable Tensile Strength (N/10mm belt width)	Specific Belt Stiffness Steel Reinforced (Per unit width/length)	Specific Belt Mass (per 10mm belt width, steel reinforced)	Min. # of Teeth on Pulley / Flat Idler Min. Ø no back bending	Min. # of Teeth on Pulley / Flat Idler Min. Ø with back bending
HTD-Series	HTD 8M	M V	- -	- -	- -	0.058 kg/m	 16 / 40mm	 16 / 60mm