



Open-Ended "M"

Specifications

Widths (mm) <small>In between widths available</small>	25	32	50	75	100
Lengths	Any lengths available - Stock rolls 50 meters				
Available Options	Nylon coating tooth side (PAZ) one side only				
Tension Member Options	Steel standard Hi-flex steel VA301 Stainless steel VA316 Hi-flex Stainless steel Kevlar®				



Spliced and Welded "V"

Specifications

Widths (mm) <small>In between widths available</small>	25	32	50	75	100
Min. Joined Length (mm) <small>Increasing in one tooth increments</small>	1,200				
Available Options	Nylon coating tooth side (PAZ) one side only				
Tension Member Options	Steel standard Hi-flex steel VA301 Stainless steel VA316 Hi-flex Stainless steel Kevlar®				

Specifications

Timing Belt	Pitch (mm)	Code	Ultimate Tensile Strength (N/10mm belt width)	Maximum Allowable Tensile Strength (N/10mm belt width)	Specific Belt Stiffness Steel Reinforced (Per unit width/length)	Specific Belt Mass (per 10mm belt width, steel reinforced)	Min. # of Teeth on Pulley / Flat Idler Min. Ø no back bending	Min. # of Teeth on Pulley / Flat Idler Min. Ø with back bending
Double Sided Series	T20 DL	M V	5600 -	1400 700	3.50 x 10 ⁵ N -	0.100 kg/m	 25 / 150mm	 25 / 180mm

Ordering Example: Polyurethane Timing Belt

[WIDTH] [PITCH] / [LENGTH] [CONSTRUCTION]

75 T20 DL / 4000 M