



Open-Ended "M"



Specifications

Widths (mm) In between widths available	4	6	10	16
Lengths	15,000	12,000	8,000	5,000
Available Options	N/A			
Tension Members	Kevlar® standard			

Spliced and Welded "V"



Specifications

Note:	Spliced and welded T2 timing belts are not readily in stock. Contact our customer service department at 732-460-9500 for more information.
--------------	--

Specifications

Timing Belt	Pitch (mm)	Code	Ultimate Tensile Strength (N/10mm belt width)	Maximum Allowable Tensile Strength (N/10mm belt width)	Specific Belt Stiffness Steel Reinforced (Per unit width/length)	Specific Belt Mass (per 10mm belt width, steel reinforced)
T-Series	T2	M	360	90	-	0.012 kg/m
		V	-	-	-	

Minimum Number of Pulley Teeth and Idler Diameter

Pitch (mm)	Min. # of Pulley Teeth (no back bending)	Min. # of Pulley Teeth (with back bending)	Min. Diameter of Flat Idler running on tooth side (mm)	Min. Diameter of Flat Idler running on belt back (mm)
T2	10	18	15	15

Ordering Example: Polyurethane Timing Belt

[WIDTH] [PITCH] / [LENGTH] [CONSTRUCTION]
 20 T2 / 256 SFX